



Electrical Commercial and Industrial

[Products](#) | [Documentation & Literature](#) | [News & Tradeshows](#) | [Support](#)

[United States](#) > [Energy](#) > [Electrical Commercial and Industrial](#) > [Products](#) > [Electrical Commercial & Industrial Products Catalog](#) > [Electrical Wire Connectors and Tools](#) > [Insulation Displacement Connectors and Tools](#) > [3M™ Scotchlok IDC Connectors for Communication Applications](#) > [3M™ Scotchlok™ IDC Butt Connector UY2-D/Bulk](#)

[Find An Account Rep](#)

[Where To Buy \(Find A Distributor\)](#)

[Contact Us](#)

3M™ Scotchlok™ IDC Butt Connector UY2-D/Bulk

3M ID 80610578264

[Print](#)



Dry for PIC, Pulp or Paper Cable Applications, 2 wire, 19-26 AWG, 2.08mm/.082" Maximum Insulation O.D., Polypropylene

Need Help?

Questions? We can help
[Contact Us](#)



Like [Sign Up to see what your friends like.](#)

Overview | **Documents**

The UY2's two ports accept any two solid copper conductor combinations of 19-26 AWG (0.9 mm - 0.4 mm) filled or air core cable with a maximum insulation O.D. of .082" (2.08 mm). The wires joined can be different wire gauges. Factory inserted sealant ins

Specifications

Applications	Dry
Cable Type	PIC, PULP, PAPER
Connection Type	Butt
Connector Style	Insulation Displacement
Connector Type	Butt/2 Conductor
Flame Retardant	Yes
Insulation Outside Diameter	0.082 Inch
Maximum Wire Gauge	19 AWG
Minimum Wire Gauge	26 AWG
Product Family	IDC for Communications Applications
Trademark	Scotchlok